



BISON GEAR

FENDER PLATES INEOS GRENADE & QUARTERMASTER INSTALLATION GUIDE

FENDER-GRND





BISON GEAR

💡 Before you start

Familiarize yourself with these instructions. Ensure that all listed parts and hardware are present in package. Gather the required tools.

⚙️ Parts list

No.	PART	QTY	IMAGE	
1	Left Fender Plate	1		<input checked="" type="checkbox"/>
2	Left Fender Plate	1		<input type="checkbox"/>
3	Ø4 Rivet	12		<input type="checkbox"/>
4	Isopropyl alcohol bottle	1		<input type="checkbox"/>

✖️ List of necessary tools¹:

- Rivet gun
- 4.1 / 4.2 drill bit
- Drill
- Tape
- Wipe

¹ NOT INCLUDED IN THE SET



BISON GEAR

⚙️ Installation:

Before you start the assembly read all the instructions carefully to ensure the product is installed correctly.

1. Position the fender plate on the car's fender.



2. Mark the position of the part by taping one of its sides to the car.
3. Lift the plate and remove the film from the double-sided tape on the bottom side of the product.
4. Clean and degrease the area below the plate thoroughly, **use the included isopropyl alcohol**.
5. Glue the fender plate down.
6. Drill 6 holes into the fender.
7. Use a rivet gun and included rivets to secure the plate.

Repeat all the steps on the other side.



BISON GEAR

Have a great time with Bison Gear products!



Email: contact@bison-gear.com

Phone: **+48 505 642 981**